



Husky®

1025

HIGH PERFORMANCE UHS PREMIUM FLOOR FINISH

UHS floor finish. Provides ultra-rich wet-look shine with less labor for professional looking floors. Combines the industry's most contemporary acrylic copolymer technology, synergistically balanced with non-slip waxes to deliver unmatched gloss levels. Highly repairable floor finish. Designed for UHS (ultra high speed) burnishing. Meets industry standards for slip resistance.

FORMULA FEATURES

- ▶ High Non-volatile Solids
- ▶ Deep, Wet-look Gloss
- ▶ Exceeds ASTM D 2047
- ▶ Increased Detergent Resistance
- ▶ Easily Top Coated
- ▶ Non Yellowing
- ▶ Excellent Black Heel Mark Resistance

APPLICATIONS *READY TO USE

- ▶ For use on resilient tile, finished concrete and terrazzo floors to seal and create a durable smooth surface.
- ▶ For facilities that burnish often.

AREAS OF UTILIZATION

- ▶ Super Markets
- ▶ Shopping Malls
- ▶ Grocery Stores
- ▶ Hospitals
- ▶ Universities
- ▶ Department Stores
- ▶ Nursing Homes
- ▶ Institutions
- ▶ Show Rooms

OTHER LIQUID / AEROSOL FORMULA CATEGORIES

- ▶ Restroom Care
- ▶ Skin Care
- ▶ Odor Control
- ▶ Health Care
- ▶ Industrial Care
- ▶ Carpet Care
- ▶ Specialty Products

Husky® 1025 HIGH PERFORMANCE UHS PREMIUM FLOOR FINISH

DIRECTIONS

PRODUCT DATA



1. Before applying floor finish, make sure that the floor surface is properly prepared. If the floor has been stripped, all residual stripper should be removed.
2. Always apply thin coats using a clean mop.
3. Allow floor finish to dry sufficiently before walking on it or applying additional coats. For standard conditions, allow at least 30 to 40 minutes. For thorough drying in poor ventilation areas, dry times may be extended.
4. Repeat steps two and three for additional coats.

Styrenated Acrylic Polymer Base
 Dual Cross Link/Metal Interlock
 Removes Easily
 Slip Resistant
 Superior Adhesion
 DOT Regulated
 VOC Compliant

YES	NO
X	
X	
X	
X	
X	
X	X

Maintenance/Formula/Facility Recommendation Matrix

Zone	Maintenance	Facility	1018	1020	1022	1025	1030
ZONE 1	Low Maintenance • Less than one buff or burnishing per week. • Customer typically wants a gloss level (7-9) to hold for extended period. Gloss Level: Initial: 7-8 • Post-Burnish: 8-9	Classrooms Budget/Staff Constrained Facility Restaurant Bars C-Stores	█				
ZONE 2	Intermediate Maintenance • One to five buff or burnishings per week. • Customer expects good initial gloss level with good reparability. Gloss Level: Initial: 6-8 • Post-Burnish: 8-10	Nursing Homes, Colleges Long Term Care Facilities Regional Medical Centers Urgent Care Facilities Government Offices, Grocery Stores Larger Restaurants, Drug Stores Retail Shops, Strip Malls		█	█		█
ZONE 3	High Maintenance • Five or more buff or burnishings per week. • Customer demands reparability with critically high gloss levels. Gloss Levels: Initial: 9 • Post-Burnish: 9-10	Hospitals, Supermarkets Office Lobbies, Show Rooms Museums, Universities Shopping Malls, Mega/Super Stores				█	

PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point	212° F
Specific Gravity (H ₂ O=1)	1.025-1.040
Vapor Pressure (mm Hg.)	N/E
Percent Volatile By Weight (%)	75%
pH (conc.)	8.2-2
Evaporation Rate (H ₂ O=1)	1
Solubility in Water	Complete
Color	White Liquid
Fragrance	Acrylic

PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled:

Wear appropriate protective equipment. If possible, contain spill and collect in an approved container. Rinse affected area thoroughly with water. Keep product out of storm sewers or waterways. Hold for disposal.

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. If possible, triple rinse container and recycle.

Precautions To Be Taken In Handling And Storing: Avoid contact with skin or eyes. Avoid breathing vapor, spray or mist. Store in original container, in cool dry place with adequate ventilation. Keep container tightly closed when not in use.

Other Precautions: Use only according to label directions. If unsure about safe use, contact your supervisor immediately.

