



ULTRA VERSATILE PREMIUM FLOOR FINISH

1022

SPECIFICATIONS:

Dilution	RTU
pH Level	8.2 – 9.2
Color	White
Fragrance	Acrylic

Premium ingredients enable **HUSKY 1022** to compete with high solids finishes.



Our most versatile and easy-to-apply floor finish is ideal for a variety of maintenance programs. Provides a brilliant gloss for terrazzo, vinyl, vinyl composition, and other resilient tile. Meets or exceeds ASTM slip resistant requirements. Contains 22% non-volatile solids.

FORMULA FEATURES:

- Brilliant, Wet-Look Gloss
- Exceptional Leveling
- Fast & Easy Application
- Dries Quickly
- Low Odor
- Non-Yellowing
- VOC CARB Compliant
- Superb Repairability – May be Used with 1000 – 2500 RPM Equipment.
- Provides Resistance to Scratches, Scuffs and Heel Marks
- Exceeds Industry Standards for Slip Resistance

RECOMMENDED FOR:

Use in ultra high-speed maintenance programs to provide high gloss levels to resilient tile, rubber, and terrazzo floors.

DIRECTIONS:

Initial Application

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse floor thoroughly and allow to dry.
3. Using a clean mop, apply a thin, uniform coat of finish. Allow to dry thoroughly (30 – 40 minutes). Apply additional coats in the same manner and let dry. For very porous floors, an initial coat of floor sealer is recommended.

Day-To-Day Maintenance

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner such as Husky 702 following label directions. For accumulated soil, lightly scrub as required.
3. To repair finish, spray buff or mop on restorer using an appropriate buffing pad, or top coat following Step 3 above.