



HIGH SOLIDS PREMIUM FLOOR FINISH

1030

SPECIFICATIONS:

Dilution	RTU
pH Level	8.2 – 9.2
Color	White
Fragrance	Acrylic

High-solids premium formula means **LESS COATS** are required, resulting in **LESS LABOR**, thereby lowering the total cost of application!



Ultra-high solids floor finish is highly durable and requires fewer coats to achieve exceptional gloss. Ideal for low to intermediate maintenance programs. Can be used on terrazzo, vinyl, vinyl composition, and other resilient tile flooring. Meets or exceeds ASTM slip resistance requirements. Contains 30% non-volatile solids.

FORMULA FEATURES:

- High Solids
- Highly Durable
- Fewer Coats Required for an Exceptional Gloss
- Dries Bright
- Non-Yellowing
- VOC CARB Compliant
- Protects against Scuffs, Scratches, and Black Heel Marks.
- May be Utilized with Equipment Ranging from 1000 – 2600 rpm
- Ideal for Low - Medium Maintenance Programs
- Exceeds Industry Standards for Slip Resistance

RECOMMENDED FOR:

For use on resilient tile, finished concrete and terrazzo floors to provide long-lasting gloss levels.

DIRECTIONS:

Initial Application

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse floor thoroughly and allow to dry.
3. Using a clean mop, apply a thin, uniform coat of finish. Allow to dry thoroughly (30 – 40 minutes). Apply additional coats in the same manner and let dry. For very porous floors, an initial coat of floor sealer is recommended.

Day-To-Day Maintenance

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner following label directions. For accumulated soil, lightly scrub as required.
3. After cleaning, burnish floor as needed to maintain gloss. Use only ultra high speed buffing pads.