

Ultra durable, high gloss floor finish formulated for easy application. Leaves a bright gloss right off the mop. Easily restored with a top scrub and recoat and can be burnished with high speed and propane equipment. Excellent scuff and black heel mark resistance. Repairs easily. Product is non-yellowing. Designed for all types of resilient tile and terrazzo flooring.

DIRECTIONS FOR USE:

Initial Application

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse floor thoroughly and allow to dry.
3. Using a clean mop, apply a thin, uniform coat of finish. Allow to dry thoroughly (30 to 40 minutes). Apply additional coats in the same manner and let dry. For very porous floors, an initial coat of floor sealer is recommended.

NOTE: To avoid product contamination, do not return any unused material to original container.

Day-To Day Maintenance

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner following label directions. For accumulated soil, lightly scrub as required.
3. After cleaning, burnish or restore floor as needed to maintain gloss.

NOTE: Water or other foreign substances will cause any floor finish to become slippery. **ALWAYS** use a "Wet Floor" sign when moisture is present.

SPECIAL INSTRUCTIONS:

Engineered for safety. Exceeds industry standards for static coefficient of friction (ASTM D2047).

For more ingredient information visit: canberracorp.com.

Manufactured By:
CANBERRA CORPORATION
3610 N. Holland-Sylvania Rd.
Toledo, OH 43615
P 419-841-6616 • TF 800-832-8992
canberracorp.com



WARNING: Suspected of damaging the unborn child.
ATTENTION: Susceptible de nuire à l'enfant à naître.

PRECAUTIONARY STATEMENTS: Obtain special instructions before use. Wear protective gloves, clothing, and eye protection. If exposed or concerned: Get medical advice/attention. Store locked up. Dispose of container to industrial combustion plant.

See First Aid Measures - Section 4 on SDS for more detailed information.

CONSEIL DE PRUDENCE: Se procurer les instructions avant utilisation. Porter des gants de protection, des vêtements de protection, un équipement de protection des yeux. En cas d'exposition prouvée ou suspectée: Consulter un médecin. Garder sous clef. Éliminer le contenant dans une installation de combustion industrielle

Voir les mesures de premiers soins - Section 4 sur FDS pour des informations plus détaillées.

For Industrial and Institutional Use Only
Keep From Freezing

060822
Label# 1652B



1026

DRY BRIGHT FLOOR FINISH

High bright gloss

Retains wet look gloss after multiple floor scrubs

Easily restored with top scrub and recoat

Non-yellowing, scuff and scratch resistant

Low maintenance requirements

**KEEP OUT OF
REACH OF CHILDREN**

WARNING

See hazard and
precautionary statements
on reverse side.
See SDS for complete
safety information.

NET CONTENTS:

One Gallon (128 fl. oz.) 3.78 liters

060822
Label# 1652F