



HUSKY® 418 MOLD CONTROL

SPECIFICATIONS:

Registrations	EPA Registered Fungicide
Dilution	RTU
pH Level	11.1 – 11.5
Color	Colorless
Fragrance	Odorless

Use **HUSKY 416** to remove mold and mildew stains then apply **HUSKY 418** to prevent future mold growth.



EPA registered solution that eliminates and stops mold without harmful chemicals. This colorless, odorless solution is used for mold clean-up and prevention, disaster restoration, and pre-treatment of building materials. It dries to form an invisible antimicrobial shield that encapsulates and physically crushes mold spores. The antimicrobial barrier remains on surfaces to provide continued protection against further mold growth. Can be used on virtually all surfaces including wallboard, wood, plaster, concrete, metal, tile, grout, fabric, upholstery and furniture.

FORMULA FEATURES:

- Eliminates Existing Mold and Mildew
- Prevents Mold Growth
- Kills Musty Odors
- Safe for Use on Hard and Soft Surfaces, Including Fabrics
- Contains No Bleach, Ammonia, Alcohol or VOCs
- Can be Applied with Trigger Sprayer, Mop, Pump-Up Sprayer, or Pressure Washer

RECOMMENDED FOR:

- Fabric
- Upholstery
- Wallboard
- Wood
- Plaster
- Concrete
- Metal
- Tile
- Grout
- Exterior Siding and Decking

READY TO USE – DO NOT DILUTE:

This product inhibits mold growth on wood, wallboard, concrete, masonry (cinder block, fabric and building materials that have been subjected to wet environments. Before applying, remove visible mold growth and correct conditions favorable to mold growth.

PREVENTATIVE TREATMENT:

To inhibit mold and mildew growth on surfaces:

- Apply this product on area until evenly wet.
- To promote drying, wipe off excess wetness.
- Allow treated surfaces to dry completely.

REMEDIAL TREATMENT:

Areas of growth less than 30 square feet (area of a single wall panel) can normally be remediated easily. Apply this product to retard the growth and spread of fungal spores until the area can be thoroughly cleaned and remediated.

If ceiling tiles or other easily removable items are moldy, remove them, seal in a plastic bag and dispose with normal trash.

If the surface is not easily replaceable:

- 1) Clean surface soil from contaminated area with this product. Remove as much dirt and mold as possible and ensure surface is thoroughly dried.
- 2) Apply this product on area until evenly wet.
- 3) To promote drying, wipe off excess wetness.
- 4) Allow treated surfaces to dry completely. This product must come in direct contact with mold to be effective.

REAPPLICATION:

Reapply weekly or when growth or odor reappears. Determine and correct the cause of re-growth and ensure surface is thoroughly dried before reapplication. Reapply this product if surfaces are washed or painted.

COVERAGE: Varies with application method:

Fogging:	1400 sq. ft. per gallon (20 x 20 room with 8 ft. ceilings -all surfaces)
Sprayer:	800 - 1000 sq. ft. per gallon
Dip:	500 sq. ft. surface per gallon
Mop/Roller:	1100 sq. ft. per gallon

Available under Private Label only in California.