



FLEETWASH & PRESSURE SPRAYER CONCENTRATE

445

SPECIFICATIONS:

Dilution	2 - 12 oz. per gal.
pH Level	12.0 – 13.0
Color	Colorless
Fragrance	Mild

Refer to the
DILUTION CHART
for the recommended
dilution ratio
for each surface.



Formulated for heavy-duty vehicle cleaning and other maintenance tasks. Easily cuts grease, oils, road film, and bugs without streaking or leaving filmy residue. May be used with a broad range of fleet maintenance programs including manual, power washing, and automatic equipment.

FORMULA FEATURES:

- Fast Acting
- Non-Streaking
- Free Rinsing
- May be Used with Hot or Cold Water
- Can be Used with Manual, Power Wash, or Automatic Equipment

RECOMMENDED FOR:

- Commercial Fleets (Cars, Trucks, Buses)
- Car/Truck Washes
- Painted or Enamel Surfaces
- Linoleum
- Asphalt
- Rubber and Vinyl Flooring
- Chrome
- Ceramic Tile
- Terrazzo /Marble
- Building Exteriors
- Aluminum / Stainless Steel

DIRECTIONS:

- Product should be diluted according to application.
- Apply with spray equipment, brush, mop, or other equipment.
- Allow solution to penetrate, then scrub (if necessary) and rinse with water.

DILUTION CHART

Light Vehicle Cleaning	1:60	(2 oz./gal)
Moderate Vehicle Cleaning	1:20	(6.4 oz./gal)
Heavy Vehicle Cleaning	1:10	(12 oz./gal)
Painted or Enameled Surfaces.....	1:60	(2 oz./gal.)
Ceramic Tile/Porcelain/Laminated Plastics	1:60	(2 oz./gal.)
Aluminum/Stainless Steel	1:60	(2 oz./gal.)
Linoleum, Asphalt, Rubber and Vinyl Flooring	1:50	(2.5 oz./gal.)
Terrazzo/Marble.....	1:50	(2.5 oz./gal.)
Leather/Plastic/Vinyl.....	1:50	(2.5 oz./gal.)
Steel/Garbage Cans/Blinds	1:50	(2.5 oz./gal.)
Fiberglass	1:50	(2.5 oz./gal.)
Painted Walls.....	1:40	(3 oz./gal.)
Woodwork/Baseboards/Furniture.....	1:40	(3 oz./gal.)
Building Exteriors	1:10	(12 oz./gal.)