



BUTYL FREE LOW ODOR UHS FLOOR STRIPPER

706

SPECIFICATIONS:

Dilution	1:10 - 1:4
pH Level	13.0 – 14.0
Color	Dye Free
Fragrance	Mild
Coverage per gal.	750 - 1000 sq. ft.

This low odor stripper is perfect for floor finishes that have been **MAINTAINED with PROPANE OR HIGH SPEED BURNISHERS.**



This low-odor floor cleaner and stripper efficiently removes layers of floor finish and sealer from resilient tile flooring without the use of butyl or strong ammonia odor. No residue is left behind to interfere with subsequent finish application. Ideal for environments sensitive to odor, such as healthcare facilities.

FORMULA FEATURES:

- Removes Multiple Layers of Finish from Resilient Flooring
- Low-Odor, Easy to Work with
- Leaves No Residue
- Reduces Costs When Used at 1:10 Dilution for Normal Build-Up.

RECOMMENDED FOR:

Healthcare applications and areas with low ventilation where odors are a concern.

DIRECTIONS:

- Dilute with cold water as follows:
 - Regular Build-Up 1:10
 - Heavy Build-Up 1:4
- Apply liberally to small area of floor, making sure the surface remains wet until removed.
- Allow to remain wet for at least 10 minutes.
- Agitate with single disc floor machine and black pad .
- Pick up with mop, wet vac, or automatic scrubber.
- Allow floor to dry completely. If slight amount of dust remains on surface, remove with dry dust mop or fresh damp mop.