

Excellent surface penetration, quickly fills pores and seals tile floors. Levels beautifully, providing exceptional durability, protection, and adhesion properties. Can be removed using a special stripper at specified use dilution. Resists stains such as iodine, betadine, mustard, ketchup, coffee, tea, chocolate, rust, Kool-Aid and other dyed products.

DIRECTIONS FOR USE:

Initial Application

1. Remove all old finish from floor. For new floors, stripping of factory applied finish is necessary. Rinse well and allow to dry.
2. Using a clean mop, or lambs' wool applicator, apply sealer in a thin, uniform coat. Allow to dry thoroughly, (30 to 40 minutes). For very porous floors and higher base gloss, a second uniform coat should be applied.
3. Allow floor to dry completely, then apply floor finish in thin, uniform coats.

PERFORMANCE DATA:

Approximate Coverage.....2000-2500 sq. ft./gal.
 Adhesion.....Excellent
 Finish Compatibility.....Excellent
 Water Resistance.....Excellent
 Detergent Resistance.....Excellent
 Permanent.....Yes, can only be removed with special strippers.
 Application: Resilient tile floors, quarry, terrazzo floors, sealed wood floors, many kinds of concrete floors

NOTE: Water or other foreign substances will cause any seal to become slippery. **ALWAYS** use a "Wet Floor" sign when moisture is present. To avoid product contamination, do not return any unused material to original container.

SPECIAL INSTRUCTIONS:

Engineered for safety... Exceeds industry standards for static coefficient of friction (ASTM D2047).

CONTAINS: Water CAS# 7732-18-5, Styrene Acrylic Copolymer CAS# N/A, Diethylene Glycol Ethyl Ether CAS# 111-90-0, Diethylene Glycol Methyl Ether CAS# 111-77-3, Tributoxy Ethyl Phosphate CAS# 78-51-3.

Manufactured By:
CANBERRA CORPORATION
 3610 N. Holland-Sylvania Rd.
 Toledo, OH 43615
 P 419-841-6616 • F 419-841-7597

PRECAUTIONARY STATEMENTS: May cause eye irritation. Avoid contact with eyes. Wash hands after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation occurs: Get medical advice/attention.

See First Aid Measures - Section 4 on SDS for more detailed information.

CONSEIL DE PRUDENCE: Peut provoquer une irritation des yeux. Éviter le contact avec les yeux. Se laver les mains après manipulation.

EN CAS DE CONTACT AVEC LES YEUX: Rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact, si présent et facile à faire. Continuer à rincer. Si l'irritation oculaire survient: Consulter un médecin.

Voir les mesures de premiers soins - Section 4 sur FDS pour des informations plus détaillées.

For Industrial and Institutional Use Only
Keep From Freezing



101514-05



SEMI-PERMANENT RESILIENT FLOOR & CONCRETE SEALER

1000

Acrylic floor sealer

Exceptional durability

Quickly fills pores

Level's easily

**KEEP OUT OF
REACH OF CHILDREN
CAUTION**

See hazard and
 precautionary statements
 on reverse side.
 See SDS for complete
 safety information.

NET CONTENTS:
One Gallon (128 fl. oz.) 3.78 liters

101514-05