

Seals terrazzo, vinyl, vinyl composition and other resilient tile. Excellent adhesion and compatibility with other finishes. A solid base coat for premium finishes, providing low color, high depth-of-gloss results on terrazzo, travertine, marble, asphalt tile, vinyl composition, linoleum and other resilient floors.

#### DIRECTIONS FOR USE:

##### Initial Application

1. Remove all old finish from floor. For new floors, stripping of factory applied finish is necessary. Rinse well and allow to dry.
2. Using a clean mop, apply sealer in a thin, uniform coat. Allow to dry thoroughly, (30 to 40 minutes). For very porous floors and higher base gloss, a second uniform coat should be applied.
3. Allow floor to dry completely, then apply floor finish in thin, uniform coats.

**NOTE:** To avoid product contamination, do not return any unused material to original container.

##### Day-To-Day Maintenance

1. Keep floor clean and free from dust and grit for maximum durability.
2. Maintain finish with appropriate method. See finish label for direction.

**NOTE:** Water or other foreign substances will cause any sealer to become slippery. **ALWAYS** use a "Wet Floor" sign when moisture is present.

##### SPECIAL INSTRUCTIONS:

Engineered for safety. Exceeds industry standards for static coefficient of friction (ASTM D2047).

**CONTAINS:** Water CAS# 7732-18-5, Polyacrylate CAS# N/A, Glycol Ether CAS# 111-90-0, TBEP CAS# 78-51-3.

Manufactured By:  
**CANBERRA CORPORATION**  
3610 N. Holland-Sylvania Rd.  
Toledo, OH 43615  
P 419-841-6616 • F 419-841-7597

**PRECAUTIONARY STATEMENTS:** May cause eye irritation. Avoid contact with eyes. Wash hands after handling.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation occurs: Get medical advice/attention.

See [First Aid Measures - Section 4](#) on SDS for more detailed information.

**CONSEIL DE PRUDENCE:** Peut provoquer une irritation des yeux. Éviter le contact avec les yeux. Se laver les mains après manipulation.

**EN CAS DE CONTACT AVEC LES YEUX:** Rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact, si présent et facile à faire. Continuer à rincer. Si l'irritation oculaire survient: Consulter un médecin.

Voir [les mesures de premiers soins - Section 4](#) sur FDS pour des informations plus détaillées.

**For Industrial and Institutional Use Only**  
**Keep From Freezing**



011703-06



1001

# VERSATILE PREMIUM FLOOR SEALER

Acrylic based floor sealer

Excellent adhesion

Compatible with multiple finishes

Easy to strip

## KEEP OUT OF REACH OF CHILDREN CAUTION

See hazard and precautionary statements on reverse side.

See SDS for complete safety information.

#### NET CONTENTS:

One Gallon (128 fl. oz.) 3.78 liters

011703-06