



SEMI-PERMANENT RESILIENT FLOOR & CONCRETE SEALER

1000

SPECIFICATIONS:

Dilution	RTU
pH Level	7.5 – 8.5
Color	White
Fragrance	Acrylic

TOUGH, ACRYLIC FLOOR SEALER

is ideal for use on concrete in light – medium traffic areas where it will be left on the floor for extended time periods.



Semi-permanent acrylic floor sealer quickly fills and seals resilient tile, terrazzo and concrete floors making a smooth, durable surface for improved dust control, floor finish adhesion and high gloss. Can be removed with a rinse-free stripper. Exceeds ASTM slip resistance requirements.

FORMULA FEATURES:

- Semi-Permanent Performance
- Improves Base for Floor Finish
- Reduces Concrete Dusting
- Resists Stains
- Can be Used for Top Scrub and Recoat
- Exceeds Industry Standards for Slip Resistance
- VOC CARB Compliant

RECOMMENDED FOR:

Resilient tile, finished concrete and terrazzo floors to seal and create a smooth, durable surface.

DIRECTIONS:

- Remove all old finish from floor. For new floors, stripping of factory applied finish is necessary. Rinse well with clean water and allow to dry.
- Using a clean dry mop, apply sealer in a thin, uniform coat.
- Allow to dry thoroughly (30 to 40 minutes). For very porous floors and higher base gloss, a second uniform coat should be applied.
- Allow floor to dry completely, then apply floor finish in thin, uniform coats