



VERSATILE PREMIUM FLOOR SEALER

1001

SPECIFICATIONS:

| | |
|-----------|-----------|
| Dilution | RTU |
| pH Level | 8.2 – 9.2 |
| Color | White |
| Fragrance | Acrylic |

Use as a base for **FLOOR FINISH** on concrete, terrazzo, vinyl, vinyl composition and other resilient tile flooring.



Durable, acrylic floor sealer quickly and easily fills and seals concrete, terrazzo, vinyl, vinyl composition, and other resilient tile flooring pores. Exceeds ASTM slip resistance requirements.

FORMULA FEATURES:

- Provides Excellent Base for Floor Finish
- Reduces Concrete Dusting
- Stain Resistant
- Exceeds Industry Standards for Slip Resistance
- Low Odor
- VOC CARB Compliant

RECOMMENDED FOR:

Use on resilient tile floors to seal and create a smooth, medium gloss finish.

DIRECTIONS:

- Remove all old finish from floor. For new floors, stripping of factory applied finish is necessary. Rinse well with clean water and allow to dry.
- Using a clean dry mop, apply sealer in a thin, uniform coat.
- Allow to dry thoroughly (30 to 40 minutes). For very porous floors and a higher base gloss, a second uniform coat should be applied.
- For best results, apply 2 – 3 uniform coats of acrylic finish on top of sealer.