



# DRY BRIGHT FLOOR FINISH

1026

## SPECIFICATIONS:

Dilution	RTU
pH Level	8.0 – 9.0
Color	White
Fragrance	Acrylic

Easily restored with a  
**TOP SCRUB  
AND RECOAT,**  
reducing the need for  
a total strip-out.



Ultra-durable, high-gloss floor finish is ideal for low maintenance programs. Formulated for easy application, Husky 1026 leaves a bright gloss right off the mop. This high-solids finish is scuff and scratch resistant and retains a wet-look gloss even after multiple floor scrubs. It is easily restored with a top scrub and recoat and can be burnished with high speed and propane equipment.

## FORMULA FEATURES:

- Highly Durable
- Leaves a Bright Gloss From Initial Application
- Extended Gloss Even After Multiple Floor Scrubs
- Clear Polymers
- Non-Yellowing
- Scuff and Scratch Resistant
- High Speed and Propane Burnishable
- Easily Restored with Top Scrub and Recoat
- Ideal for Low Maintenance Programs
- Exceeds Industry Standards for Slip Resistance
- VOC CARB Compliant

## RECOMMENDED FOR:

For use on resilient tile, finished concrete, and terrazzo floors providing long-lasting gloss levels in facilities with low maintenance programs.

## DIRECTIONS:

### Initial Application

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse floor thoroughly and allow to dry.
3. Using a clean mop, apply a thin, uniform coat of finish. Allow to dry thoroughly (30 – 40 minutes). Apply additional coats in the same manner and let dry. For very porous floors, an initial coat of floor sealer is recommended.

### Day-To-Day Maintenance

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner following label directions. For accumulated soil, lightly scrub as required.
3. To repair finish, spray buff or mop-on restorer using an appropriate buffing pad, or top coat following Step 3 above.