



Guardian

HUSKY® 1002

Durable Floor Finish

High-gloss, durable floor finish is perfect for a variety of maintenance programs. Advanced polymer technology provides excellent burnish response and maximum gloss retention. Exceptional leveling characteristics and easy application for terrazzo, vinyl, vinyl composition and other resilient tile flooring.

Directions

Initial Application

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse floor thoroughly and allow to dry.
3. Using a clean mop, apply a thin, uniform coat of finish. Allow to dry thoroughly (30-40 minutes). Apply additional coats in the same manner and let dry. For very porous floors, an initial coat of floor sealer is recommended.

NOTE: To avoid product contamination, do not return any unused material to original container.

Day-To-Day Maintenance

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner following label directions. For accumulated soil, lightly scrub as required.
3. After cleaning, burnish or restore floor as needed to maintain gloss.

NOTE: Water or other foreign substances will cause any floor finish to become slippery. ALWAYS use a "Wet Floor" sign when moisture is present.



Proven gloss retention.

Specs

Dilution: RTU
pH Level: 8.0-9.0
Color: White
Fragrance: Acrylic
Pack Types: Gal, 5 Gal Bag-in-Box

Features

- Durable Shine
- Maximum Gloss Retention
- Excellent Burnish Response and Detergent Resistance
- Soil & Scuff Resistant

Recommended For

- All types of resilient flooring