



EverGuard+

HUSKY® 1003

Extended Wear Floor Finish

Ultra durable, long-wearing formula offers a brilliant gloss for all types of resilient flooring. Advanced polymer technology provides maximum gloss retention and superior resistance to detergents, soils and scuffs. Self-leveling formula delivers smooth application response. Ideal for a variety of maintenance programs.

Directions

Initial Application

1. Remove all old wax and floor finish with appropriate stripper.
2. Rinse floor thoroughly and allow to dry.
3. Using a clean mop, apply a thin, uniform coat of finish. Allow to dry thoroughly (30-40 minutes). Apply additional coats in the same manner and let dry. For very porous floors, an initial coat of floor sealer is recommended.

NOTE: To avoid product contamination, do not return any unused material to original container.

Day-To-Day Maintenance

1. Sweep or dust mop as necessary.
2. Damp mop with proper cleaner following label directions. For accumulated soil, lightly scrub as required.
3. After cleaning, burnish or restore floor as needed to maintain gloss.

NOTE: Water or other foreign substances will cause any floor finish to become slippery. ALWAYS use a "Wet Floor" sign when moisture is present.



Extended durability and performance.

Specs

Dilution: RTU
pH Level: 8.0-9.0
Color: White
Fragrance: Acrylic
Pack Types: Gal, 5 Gal Bag-in-Box

Features

- Protective Gloss Shine
- Long-Lasting, Ultimate Wear
- Superior Gloss Retention
- Soil, Scuff & Detergent Resistant
- Exceptional Burnish Response
- Self-Leveling

Recommended For

- All types of resilient flooring